

ACTIVE TRANSPORTATION PLAN -

Existing Conditions Active Transportation Plan

Prepared for: MetroPlan Orlando

September 2023



- ACTIVE TRANSPORTATION PLAN -

Table of Contents

Introduction	1
Policies and Goals	2
MetroPlan Orlando	3
Regional Overview	7
Land Use and Key Destinations	7
Population and Jobs	7
Demographics	10
Travel Mode Share	13
Existing Road Types and Facilities	
MetroPlan Orlando Roadway Network	16
Posted Speed Limits	16
Vehicular Traffic Volumes and Travel Lanes	
Bicycle Facilities	22
Pedestrian Facilities	
Transit Facilities	
Collision Analysis	
LTS and PLOC Results	
Travel Access Analysis	
Existing Planned Facilities	
Public Participation	

Technical Appendix (Under Separate Cover)

Appendix A: Policy Assessment
Appendix B: Mode Share by City
Appendix C: Level of Traffic Stress/Pedestrian Level of Comfort Methodology
Appendix D: Accessibility Analysis Methodology
Appendix E: First Round Public Engagement Summary
Appendix F: Final Public Engagement Summary



List of Figures

_

Figure 1: Existing Population Density by Census Tract	9
Figure 2: Disadvantaged Census Tracts	12
Figure 3:MPO Roadway Network	17
Figure 4: Posted Speed Limit MPO Roadway Network	18
Figure 5: Existing Average Annual Daily Traffic	20
Figure 6: Existing Number of Travel Lanes	21
Figure 7: Existing On-Street Bicycle Facilities	26
Figure 8: Existing Off-Street Facilities	27
Figure 9: Existing Pedestrian Facilities – All Roadways in Region	29
Figure 10: Existing Transit Routes	32
Figure 11: Existing Transit Ridership Fiscal Year 2022	33
Figure 12: Pedestrian and Bicyclist KSI Crash Locations (2018 – 2022)	37
Figure 13: Existing Bicycle Level of Traffic Stress	40
Figure 14: Existing Pedestrian Level of Comfort	43
Figure 15: Existing Bicycle Accessibility Summary	46
Figure 16: Existing Pedestrian Accessibility Summary	47
Figure 17: Existing Bicycle Access and Comfort Summary	48
Figure 18: Existing Pedestrian Access and Comfort Summary	49
Figure 19: Planned On-Street Bicycle Facilities	54
Figure 20: Planned Off-Street Bicycle Facilities	55
Figure 21: Future Bicyclist Accessibility with Planned Improvements	56
Figure 22: Future Pedestrian Accessibility with Planned Improvements	57



List of Tables

_

Table 1: Population and Job Density	8
Table 2: Demographic Information	13
Table 3: Travel Mode Share	14
Table 4: Centerline Miles by Posted Speed Limit MPO Roadway Network	19
Table 5: Lane Miles of On-Street Bicycle Facilities by Posted Speed Limit	25
Table 6: Miles of Pedestrian Facilities	28
Table 7: MPO Network Sidewalk Gap Miles by Posted Speed	28
Table 8: Distinction between Golf Carts and Low-Speed Vehicles	31
Table 9: Regional Collision Data (all roadways – 2018 to 2022)	35
Table 10: LTS Score for MPO Network by Bicycle Facility Type (in miles of facility)	39
Table 11: PLOC Score for MPO Network by Pedestrian Facility Type (in miles of facility)	42
Table 12: Existing Travel Access Summary Via Predominately Low-Stress Network* – 0 -15 Minute Travel Time	50
Table 13: Existing Travel Access Summary Via Predominately Low-Stress Network* – 0 -30 Minute Travel Time	50
Table 14: Existing Travel Access Summary Via Predominately Low-Stress Network within Disadvantaged Communities – 0-15 Minute Travel Time	51
Table 15: Existing Travel Access Summary Via Predominately Low-Stress Network within Disadvantaged Communities – 0-30 Minute Travel Time	51
Table 16: Average Population in Low Stress Travel Sheds	52
Table 17: Disadvantaged Community Population in Low Stress Travel Sheds	52
Table 18: Planned Facility Types on MPO Network	53
Table 19: Future Planned System Travel Access Summary Via Predominately Low-Stress Network* – 15 Minute Travel Time	58
Table 20: Future Planned System Travel Access Summary Via Predominately Low-Stress Network* – 30 Minute Travel Time	58



Introduction

The MetroPlan Orlando Regional Active Transportation Plan (ATP): Ride & Stride 2050 will serve as a roadmap to enhance active transportation options on the MPO Roadway Network throughout Orange, Osceola, and Seminole Counties. This document summarizes the existing conditions assessment that was conducted through the lens of the Active Transportation Plan's key objectives:

- 1. Improve transportation safety outcomes for vulnerable roadway users, including pedestrians, bicyclists, and other non-auto transportation system users.
- 2. Identify a regional active transportation network that complements other travel modes, especially transit, and supports future land use patterns.
- 3. Develop a feasible project list to incorporate into the 2050 Metropolitan Transportation Plan.

Throughout this document, all references to pedestrians are inclusive of persons with disabilities who use mobility aids (i.e., scooters, manual and powered wheelchairs) to access public pedestrian walkways.

This document is organized around the following main topics:

- Policies and Goals
- Regional Overview
- Existing Road Types and Facilities
- Collision Analysis
- Level of Traffic Stress and Pedestrian Level of Comfort
- Travel Access Analysis
- Planned Facilities
- Public Participation

For some of the topics, separate memorandums have been prepared, with this document providing a summary of results and the supporting documents provided as an attachment.



Policies and Goals

To support the development of the ATP, a review of relevant plans and policies from the three Counties, 22 incorporated cities and towns, and the Florida Department of Transportation (FDOT) was conducted to identify potential barriers to plan implementation and identify policy guidance that could be incorporated into the ATP.

Overall, MetroPlan Orlando member jurisdictions have goals and policies that are supportive of providing active transportation facilities within the region. However, some potential barriers were identified that could hinder the implementation of the Active Transportation Plan: Ride & Stride 2050 equally throughout the region, including:

- Some communities with vehicle delay-based level of service policies that do not have exceptions for prioritizing bicycle and pedestrian travel along some corridors.
- Lack of supportive regulations that require new developments to provide bicycle parking and other design features that could promote higher levels of walking, bicycling and transit use over time.
- Insufficient staffing resources to implement projects identified within their jurisdiction.
- Land Development Codes that may miss opportunities to require new bicycle and pedestrian facilities to be constructed as part of development.
- Technology changes that are not considered in local planning documents, such as escooters and e-bikes.

To help overcome some of these barriers, there are opportunities as part of the plan development to provide policy language and development code templates that could be used as municipal partners update various plans in the future. Some examples include:

- Example Level of Service Exemptions
- Level of Service Standards for Active Transportation Modes
- Bicycle Parking Standards
- E-Scooter and E-Bike Ordinances

Additionally, there may be a need to develop a technical assistance program to help some jurisdictions navigate project implementation, including identification of grant programs and coordinating with FDOT and other regional/local partners to implement projects. The full plan review is provided as **Appendix A**.



The following presents relevant policies and goals from the 2045 Metropolitan Transportation Plan (2045 MTP) and potential policy refinements to consider as part of the 2050 Metropolitan Transportation Plan.

MetroPlan Orlando

Policies and goals guide how an organization makes decisions and what it prioritizes. MetroPlan Orlando's primary guiding document is the 2045 MTP (available <u>here</u>: <u>https://metroplanorlando.org/plans/metropolitan-transportation-plan/</u>). The 2045 MTP sets the goals, objectives, and project evaluation process for the organization over the coming years. Preparation of the 2045 MTP was guided by five overarching goals that collectively advance the MetroPlan Orlando vision for a *regional transportation system that safely and efficiently moves people and goods through a variety of options that support the region's vitality*. The five goals are listed below along with objectives from the 2045 MTP that a robust bicycle and pedestrian system can help accomplish. Within the Bicycle & Pedestrian Needs Assessment document, active mobility strategies are identified, with these strategies helping to inform project prioritization criteria. Based on our review of the 2045 MTP goals, objectives and active mobility strategies, opportunities for policy refinement within the 2050 MTP were developed.

• Safety and Security - provide a safe and secure transportation system for all users

2045 MTP Objectives

- Eliminate the rate and occurrence of transportation system fatalities, injuries, and crashes with high emphasis on the most vulnerable users
- Provide infrastructure and services to help prepare for, respond to, and recover from emergencies
- Prevent and mitigate transportation-related security risks
- o Improve emergency response and incident clearance times
- Increase the resiliency of infrastructure to risks, including extreme weather and environmental conditions

2050 MTP Objective Opportunities

- The 2045 MTP objectives as related to Safety and Security help advance the vision of a safer Active Transportation system in the region. Adoption of the regional Vision Zero Action Plan in 2024 will further enhance strategies to reduce the prevalence of fatal and severe injury crashes in the region.
- Reliability and Performance leverage innovative solutions to optimize system
 performance



2045 MTP Objectives

- o Improve travel time reliability on the transportation system
- Enhance and expand the region's ITS, adaptive and actively managed traffic systems
- Reduce travel time per capita (peak and off-peak travel times)
- Improve average transit on-time performance (bus and rail services)
- Adapt transportation infrastructure and technologies to meet changing traveler needs and desires

2050 MTP Objective Opportunities

- With the 2050 MTP, there are opportunities to incorporate reliability and performance standards for bicycling and pedestrian infrastructure. In specific contexts, providing increased opportunities for crossing the street, leading pedestrian intervals or bicycle detection are potential performance indicators for non-auto travel. Additionally, providing people with increased travel mode options can improve the reliability of their travel – if one mode is not available to them, there are other reasonable choices to complete a trip.
- Access and Connectivity Enhance communities and lives through improved access to opportunities

2045 MTP Objectives

- o Increase transit system frequency
- o Improve housing and employment access to high-frequency transit
- o Improve access to essential services across all modes of transportation
- Reduce per capita vehicle miles traveled (VMT)
- o Increase ridership on public transportation
- o Reduce the reliance on single-occupant vehicle travel
- Plan and develop transportation systems that reflect regional and community values

2050 MTP Objective Opportunities

 A barrier to higher transit use is the lack of safe pedestrian facilities connecting people from their origin or destination to transit facilities. The ATP also includes an accessibility analysis to identify locations in the region that have less accessibility via walking and bicycling modes. Incorporation of accessibility indicators for all travel modes could be used to identify communities in the region where walking and bicycling infrastructure should be prioritized.



• Health and Environment – Protect and preserve our region's public health and environmentally sensitive areas

2045 MTP Objectives

- Provide transportation solutions that contribute to improved public health
- Expand conservation lands and minimize land consumption for future development
- o Increase population/employment densities and mix of land uses
- Reduce per capita related air quality pollutants and greenhouse gas emissions
- o Reduce adverse health impacts associated with physical inactivity
- Plan and develop transportation systems in a manner that protects and restores the function and character of the natural environment and avoids or minimizes adverse environmental impacts
- Reduce transportation system impacts caused by stormwater issues and flooding
- Prevent disproportionate adverse effects of transportation projects on minority and low-income communities

2050 MTP Objective Opportunities

- The 2045 MTP policies are supportive of providing active transportation infrastructure to help improve public health outcomes. There are opportunities to reference providing lower stress walking and bicycling facilities to help encourage more frequent walking and bicycling trips.
- Investment and Economy support economic prosperity through strategic transportation investment

2045 MTP Objectives

- Meet industry, state, and national standards for infrastructure and asset quality, condition, and performance for all public transportation infrastructure
- Reduce per capita delay for residents, visitors, and businesses
- o Increase affordability for transportation and housing choices
- Improve transportation experience for visitors and supportive-industry workers
- \circ $\,$ Increase the number of skilled workers in Central Florida's transportation-related industries



 Promote transportation projects that expand and enhance economic prosperity

2050 MTP Opportunities

 Objectives related to reducing per-capita delay could be contrary to other goals and objectives related to safety and the provision of additional infrastructure for walking and bicycling. While reducing delay incurred by all roadway users as a result of improperly timed traffic signals may be appropriate, reducing delay through roadway widening to address periods of peak congestion may be contrary to other goals and should be carefully weighed against other strategies.

Guiding Principles

To guide the identification of specific projects, policies, and strategies, guiding principals were developed based on the existing conditions assessment described in this document, as well as project goals, feedback from the steering committee, the existing policy framework, and future policy opportunities. The three Guiding Principles include:

- **Safety** as one of the most dangerous places in America for people walking and bicycling, improving transportation safety outcomes is a key priority and all projects, policies, and strategies will be evaluated through a safety lens.
- Equity, Inclusion and Health there are disproportionate impacts in some communities related to transportation safety and health outcomes, partially due to fewer transportation options. Prioritizing active transportation improvements in communities where there has historically been less investment is a priority for the region.
- **Connectivity and Comfort** providing comfortable and direct routes of travel to a variety of land uses, including transit stops, has been identified as a priority by the steering committee and the public to access educational, employment and shopping opportunities by a variety of travel modes.



Regional Overview

Land uses, population density, demographics, and development patterns are all key components of the transportation system and how it is used. This section describes some of the non-roadway elements that are considered in the ATP planning process.

Land Use and Key Destinations

The MetroPlan Orlando region is comprised of three counties, Orange, Osceola, and Seminole, each with different development patterns and geographies that affect the operation of the transportation system. The population of this region is currently about 2.3 million people. In 2022, over 74 million visitors came to the area, making it one of the most popular tourist destinations in the world, with current tourism levels on-track to exceed prepandemic visits. This section describes existing land uses and key destinations in the region.

Orange County is a predominantly urban area that is composed of 13 incorporated cities and towns. The largest city in Orange County is Orlando, where about a quarter of the county's population lives. In addition to local schools, parks, and businesses, the county is home to regional attractions including several universities and colleges, regional hospitals, museums, professional sports stadiums, event venues, and a major international airport. There are also many recreational and wildlife areas. Orange County is also home to several world-renowned theme parks, including Disney World, Sea Word, and Universal Studios, that draw millions of visitors every year.

Osceola County is predominantly rural, with most of the population living in the northwest of the County. The County has two incorporated cities: Kissimmee and St. Cloud. There are also several unincorporated towns within the County. While much of the remaining land is comprised of private agricultural land and preservation areas, planning for several large developments are underway that will house much of the projected population growth in the region. Osceola County is close to many of the destinations in Orange County, and many visitors stay in Osceola County.

Seminole County is comprised of seven incorporated cities. The eastern border of the County is mostly agricultural and wildlife lands. The County hosts an international airport, zoo, and a wide variety of parks and recreational areas. The county prides itself on its natural resources and outdoor attractions. Many of the shared-use paths/trails in the MetroPlan Orlando region are in Seminole County.

Population and Jobs

Approximately 2.39 million people live in the MetroPlan Orlando region, with Orange County having the highest population of about 1.48 million people. According to 2022 population



estimates prepared by the Office of Economic and Demographic Research, the population of Osceola County is about 425,000 people and the population of Seminole County is about 484,000. Florida is one of the fastest growing states, with the population of the region expected to increase by about 36 percent by 2045, adding an additional 880,000 people, as summarized in **Table 1**, to the MetroPlan Orlando region. The total employment by county is also summarized, with the region providing about 1.2 million jobs. Many people who live in Osceola and Seminole Counties commute to Orange County for work.

Variable	Orange County	Osceola County	Seminole County	Regional	Notes
Existing Population	1,481,300	424,950	484,000	2,390,250	2022 Population Estimates
Projected Population (2045)	1,987,400	705,700	578,800	3,721,900	2045 population estimates
Total Employment	894,330	98,420	209,940	1,202,690	2020 LEHD
Size (square miles)	1,003	1,506	345	2,854	
Existing Average Population Density (people/square mile)	1,477	282	1,403	838	
Projected Average Population Density (people/square mile)	1,981	469	1,678	1,304	
Existing Average Job Density (iobs/square mile)	892	65	609	421	

Table 1: Population and Job Density

Notes: Longitudinal Employer-Household Dynamics (LEHD) data is based on tabulated and modeled administrative data provided states to the Census Bureau related to unemployment earnings, and the quarterly census of employment and wages. Additional information can be found here: https://onthemap.ces.census.gov/

Source: Office of Economic and Demographic Research, LEHD Data; Fehr & Peers, 2023

The existing population and job density, and projected population density were also calculated for each county, as shown on Table 1. As population density increases, higher levels of walking and bicycling may occur, as more land uses are proximate. However, the quality and perception of safety for the walking and bicycling infrastructure, along with area demographics, ultimately play a large role in an individual's decision to walk or bicycle. As the average population density by county can be misleading, especially in Osceola County where much of the land is undeveloped, the average existing population density by census tract is presented on **Figure 1**.



Existing Population Density by Census Tract





Demographics

A demographic assessment was conducted to identify key population characteristics that could contribute to an increased reliance on walking and bicycling as transportation modes. Populations that are reliant on non-auto travel modes, with limited access to walking and bicycling facilities, could have a higher risk for being involved in a crash that results in a fatal or severe injury. For the purposes of this analysis, the current MetroPlan Orlando Title VI Underserved Community Definitions were used, as documented in the Nondiscrimination Plan (document can be found <u>here: https://metroplanorlando.org/plans/nondiscrimination-language-plans/</u>). MetroPlan Orlando works to ensure that transportation decisions do not cause disproportionately high and adverse effects on low-income and minority populations – a concept known as environmental justice (EJ). A census tract must meet four of the seven indicators to be considered an EJ focus area:

- 1. Low Income A person or family whose median household income is at or below the U.S. Department of Health and Human Services poverty guidelines.
- 2. Minority Population An individual belonging to any of the following groups:
 - Black persons having origins in any of the black racial groups of Africa
 - Hispanic or Latino persons of Mexican, Puerto Rican, Cuban, Central or South American or other Spanish culture or origin, regardless of race
 - Asian American persons having origins in any of the original peoples of the Far East, Southeast Asia, or the Indian subcontinent
 - American Indian and Alaskan Native persons having origins in any of the original people of North America, South America (including Central America), and who maintain cultural identification through tribal affiliation or community recognition
 - Native Hawaiian and Other Pacific Islander persons having origins in any of the original peoples of Hawaii, Guam, Samoa, or other Pacific Islands
- 3. Aging Population Because of the increasing number of persons aged 65 and older, the aging population is increasingly being categorized as young-old (65-74), old (75-84), and oldest-old (85+).
- 4. **People with Disabilities -** Persons who have mobility and/or self-care limitations, as defined by the U.S. Census. The disability may be physical or mental.
- 5. Zero Car Households Households without automobiles or access to an automobile.
- 6. Limited English Proficiency Individuals who do not speak, read, write, or understand the English language at a level that permits effective interaction.



7. **Female Head of Household with Child -** Households led by a single mother with children under age 18.

About 42 percent of the region's population lives in a census tract that is defined as an EJ area, with almost half of the population in both Orange and Osceola counties living in an EJ area. **Figure 2** displays the number of criteria each census tract in the region meets.

Table 2 summarizes some of the key data inputs to the transportation disadvantageddesignation.

MetroPlan Orlando is in the process of updating the approach to identifying underserved communities to align with the Justice40 Initiative and other efforts underway by the US Department of Transportation (USDOT). The adopted criteria in place at the time of project prioritization will be used for this project.



FIGURE 2 Disadvantaged Census Tracts





Table 2: Demographic Information

Variable	Orange County	Osceola County	Seminole County	Regional Total	Notes
2020 Households Below the Poverty Level (%)	13.5%	13.3%	9.6%	12.5%	2020 5 Year ACS
2020 Owner Occupied Housing Units (%)	56.5%	63.5%	63.9%	59.3%	2020 Census
2020 Renter Occupied Housing Units (%)	43.5%	36.5%	36.1%	40.7%	2020 Census
2020 Owner Households with No Vehicles (%)	2.3%	3.2%	1.8%	2.3%	2020 5 Year ACS
2020 Renter Households with No Vehicles (%)	9.2%	8.8%	7.2%	8.7%	2020 5 Year ACS
2020 Under 18 Years Old (%)	22%	24%	21%	22%	2020 5 Year ACS
2020 Senior Population (%)	13.1%	14.8%	16.9%	14.2%	2020 5 Year ACS
2020 Households With 1+ Persons with a Disability (%)	22.9%	30.6%	22.3%	23.9%	2020 5 Year ACS
Population in Underserved Communities Census Tracks (%)	45%	48%	31%	42%	USDOT

Source: 2020 5 Year American Community Survey (ACS) Data and US Department of Transportation (USDOT).



Travel Mode Share

The mode of travel a person will select for a specific trip is dependent on many factors, including:

- Destination distance
- Trip purpose
- Travel costs, including parking
- Availability of a vehicle, bicycle, or transit
- Personal disability
- How many people are traveling
- Transportation infrastructure, such as the presence of sidewalks and bicycling facilities

Data for work trips is the most readily available data from the Census, which shows that most people who work in the region drive a car or carpool to their place of employment, with about three percent of residents in the region walking, biking, or taking transit to work, as shown in **Table 3.**

Table 3: Travel Mode Share

Variable	Orange County	Osceola County	Seminole County	Regional Average	Notes
2020 Average Travel Time to Work (min)	28.8	34.3	27.8	29.4	2020 5 Year ACS
2020 Percent of Workers with Travel Time to work > 30 mins	46.7%	60.4%	42.7%	48.0%	2020 5 Year ACS
2020 Workers age 16+ Means of Transportation to Work: Public transportation (excluding cab) (%)	2.0%	1.2%	0.7%	1.6%	2020 5 Year ACS
2020 Workers age 16+ Means of Transportation to Work: Bicycle (%)	0.5%	0.3%	0.2%	0.4%	2020 5 Year ACS
2020 Workers age 16+ Means of Transportation to Work: Walk (%)	1.3%	0.7%	1.0%	1.1%	2020 5 Year ACS

Source: 2020 5 Year American Community Survey Data.



With an average travel time to work of about 29 minutes, most people do not live in proximity to their place of employment such that walking or bicycling is practical. The Florida Department of Transportation (FDOT) conducted a statewide survey in 2021 related to transportation use (documented <u>here</u>:

https://fdotwww.blob.core.windows.net/sitefinity/docs/default-

source/planning/customers/2021survey.pdf?sfvrsn=1afde675_4). While the responses are only available at the FDOT district level, people in District 5, which includes the MetroPlan Orlando region, reported that about 18.5 percent walk for travel at least 4 times a week, 9 percent bicycle for travel at least 4 times a week, and about 4.5 percent use transit at least 4 times a week for travel. These results include all trip purposes, so while commute modes are one indicator of the potential level of walking and bicycling in a community, commute trips represent a small percentage of overall trips people make.

Commute mode share for each city in the region is provided in **Appendix B**. The city with the highest percentage of people who walk, bike, or take transit is the City of Eatonville, with 8 percent of residents. Based on 2020 data, approximately 27 percent of Eatonville residents live in households with income below the poverty level with about 10 percent of households not having access to a vehicle.



Existing Road Types and Facilities

This section describes the existing roadway network, including bicycle and pedestrian facilities. This information will help the project team identify opportunities for new and enhanced facilities to include in the plan. This section is divided into the following subsections:

- MetroPlan Orlando Roadway Network
- Bicycle Facilities
- Pedestrian Facilities
- Transit Facilities
- Mobility Trends

MetroPlan Orlando Roadway Network

The ATP is focused on roadways along the designated MPO Roadway network, which includes the State Highway System, major arterials, and some major collector roadways throughout the region, as shown on **Figure 3**, serving as the major transportation network within the region. This network is also known as the Federal Aid Network. While bicycle and pedestrian facilities on the non-MPO roadway network provide important connections to the regional roadway network, modifications to the non-Federal Aid Network are planned at the local level and are not included in this assessment.

Posted Speed Limits

One of the key inputs to the level of traffic stress (LTS) and pedestrian level of comfort (PLOC) analysis, which are presented in a subsequent section, is the speed at which vehicles are traveling. The speed a vehicle is driven is one of the biggest factors in the outcome of a collision. The faster a vehicle is driven, the greater the likelihood that someone will be seriously injured or killed as the result of a collision, with people walking and bicycling being disproportionately represented in crashes that result in a severe injury or fatality. Walking or bicycling adjacent to fast-moving vehicles can also be uncomfortable for some people. A summary of the existing posted speed limits on the MPO Roadway Network are shown on **Figure 4** with **Table 4** providing a summary of the lane miles for each speed category. Most roadways on the MPO Network have a posted speed limit between 35 and 45 miles per hour (mph), with slower speed roadways in downtown areas. There are many commercial corridors in the MetroPlan Orlando region with a posted speed limit of 40 mph or greater with active land uses on both sides of the street as well as transit facilities.



FIGURE 3 MPO Roadway Network





Posted Speed Limit MPO Roadway Network





Posted Speed Limit	Orange County	Osceola County	Seminole County	Regional Total
30 mph or less	260	66	65	391
35 mph to 45 mph	738	200	253	1,191
50 mph or higher	127	229	33	389
Total	1,125	495	351	1,971

Table 4: Centerline Miles by Posted Speed Limit MPO Roadway Network

Notes: Centerline Miles represent the total length of a given road from a start point to an end point. The mileage does not include the size or number of lanes nor does it include other features, like shoulders and turn lanes. Source: xGeographic Wave Database as summarized by Fehr & Peers, 2023

A consideration of where to invest in active transportation facilities and selection of the appropriate facility type is the speed at which people will be driving. On roadways with high travel speeds, a separation or physical barrier between the bicycling or walking facility would be desirable while on a slow speed roadway, less separation would be needed to provide a comfortable facility.

Vehicular Traffic Volumes and Travel Lanes

The amount of vehicle traffic and the number of travel lanes on a roadway is also an input to the LTS and PLOC analyses. Roadways with higher volumes increase potential exposure and conflicts between all roadway users, and roadways that have multiple lanes in each direction, typically designed for high levels of peak period travel, usually have excess capacity during off peak travel times that can encourage people to drive faster than the posted speed limit. **Figure 5** shows the average annual daily traffic (AADT) for roads on the MPO network and **Figure 6** shows the number of travel lanes on each roadway on the MPO network.



Existing Average Annual Daily Traffic





Existing Number of Travel Lanes





Bicycle Facilities

This section describes the type and location of existing bicycle facilities in the MetroPlan Orlando region with a focus on the MPO network, with the general extent of existing on-street bicycle facilities shown on **Figure 7** and off-street bicycle facilities shown on **Figure 8**. These maps categorize the bicycle facilities into four facility types, bike lanes, paved shoulders, side-paths, and shared-use paths/trails. More details about each category are provided below.

On-Street Bike Facilities – This category includes (see Figure 7):

- bike lanes dedicated, on-road bicycle facilities (at least four-feet wide) (Image 1),
- **buffered bike lanes** bike lanes with horizonal separation between vehicle lanes (Image 2),
- **separated bike lanes** exclusive bicycle facilities that are physically separate from the roadway and distinct from the sidewalk (Image 3), and
- **protected bike lanes** exclusive bicycle facilities that are physically separated from vehicle and pedestrian traffic by a physical barrier (Image 4).
- **Paved shoulder** roadways that do not have a dedicated bicycle facility, but that have a paved shoulder that's at least four-feet wide. These are often high-speed rural roadways with minimal cross traffic.

Prior to 2016, the minimum required width for a bicycle lane was 4-feet on FDOT facilities. Since that time, the standards have been updated to reflect a wider range of bicycle facility types, with the guidance to provide the bicycle facilities in the following priority order as conditions permit:

- 1. 7-foot buffered bicycle lane
- 2. 6-foot buffered bicycle lane
- 3. 5-foot bicycle lane
- 4. 4-foot bicycle lane

As roadways undergo periodic resurfacing, there may be opportunities to upgrade on-street bicycle facilities to current standards.

On-street facilities also include wide sidewalks (sidewalks that are at least 8-feet wide) that can be shared by people walking and bicycling (see Figure 8).

MetroPlan Orlando Active Transportation Plan Existing Conditions





Image 1: Bike Lane Example



Image 2: Buffered Bike Lane Example



Image 3: Separated Bicycle Facility Example



Image 4: Protected Bike Lane Example



Image 5: Paved Shoulder Example

MetroPlan Orlando Active Transportation Plan Existing Conditions



Off-Street Bike Facilities – This category includes (see Figure 8):

- Share-use paths/trails provide a facility that is separated from the vehicular travel way for use by bicyclists, pedestrians, skaters, wheelchair users, joggers, and other users. Conflicts between trail users and people driving exist at crossing locations. Trails are typically 12 feet wide, with a 2-foot unpaved shoulder, but can be reduced to 10 feet when there are right-of-way or environmental conditions, like a mature tree or wetlands area, that preclude a wider path (See Figure 8).
- Side paths two-way path for both bicyclists and pedestrians adjacent to a roadway. Like shared-use paths, they are typically 12-feet wide but can be reduced to 10-feet where conflicts exist, and as narrow as 8-feet for short segments where there is a constrained right-of-way. On high-speed roadways (45 mph or greater) a separation of at least 5-feet from the vehicular travel way is required per the Florida Design Manual (FDM). In Urban and constrained areas, less separation is required (See Figure 8). Wide sidewalks are a subset of side paths, where the facility provides added width (8feet) from a standard sidewalk, which is typically 5 or 6 feet.



Image 6: Shared-use path/Trail Example



Image 7: Side Path Example



Table 5 shows the number of on-street lane miles of bicycle facilities on the MetroPlan Orlando network, with an additional 128 miles of off-street trails and 151 miles of sidepaths. There are about 425 miles of on-street bicycle facilities, with about 9 percent being on roadways with a posted speed limit of 30 mph or less, 54 percent on roadways with a posted speed of 35 to 45 mph, and 37 percent on roadways with a posted speed of 50 MPH or greater. Approximately 40 percent of roadways with a speed of 50 mph or greater have bicycle lanes or a paved shoulder that can be used by bicyclists.

	Lane Miles by Posted Speed of Roadway			
Facility Type	30 mph or Less	35 to 45 MPH	50 MPH or More	
Bike Lane (4 ft +)	37	216	92	
Paved shoulder (4 ft +)	1	15	64	
Percent of Total Lane Miles by Speed (see Table 4)	9.7%	19.4 %	40.1%	
Percent of Total On- street Facilities	8.9%	54.4%	36.7%	

Table 5: Lane Miles of On-Street Bicycle Facilities by Posted Speed Limit

Source: xGeographic Wave Database as summarized by Fehr & Peers, 2023.



Existing On-Street Bicycle Facilities





FIGURE 8 Existing Off-Street Facilities





Pedestrian Facilities

Pedestrian facilities in the region are typically provided by sidewalks, side paths and shared use paths. However, there are some roadways in the region where sidewalks are only provided on one side of the street, as shown on **Figure 9** and summarized in **Table 6**. The sidewalk gaps by the posted speed limit of the roadway were assessed, as presented in **Table 7**, which shows that sidewalk gaps tend to be more prevalent on higher speed roadways. Of the MPO roadway network, approximately 26 percent of roadways do not provide any sidewalks and about 18 percent only provide sidewalks on one side of the street.

Facility Type	All Roadways (in miles)	MPO Roadway Network (in miles)
Sidewalk one side	1,590	384
Sidewalk both sides	5,169	1,084
Wide Sidewalk	466	179
Side Path	329	182
Shared-use path/trail		141

Table 6: Miles of Pedestrian Facilities

Source: xGeographic Wave Database as summarized by Fehr & Peers, 2023

Table 7: MPO Network Sidewalk Gap Miles by Posted Speed

	Sidewalk Gap Miles by Posted Speed of Roadway			
Facility Type	30 mph or Less Gap Miles / (% of MPO Network Centerline Miles)	35 to 45 MPH Gap Miles / (% of MPO Network Centerline Miles)	50 MPH or More Gap Miles / (% of MPO Network Centerline Miles)	
Sidewalk Missing	44 (11%)	203 (17%)	282 (72%)	
Sidewalk One Side	108 (28%)	223 (19%)	38 (10%)	

Source: xGeographic Wave Database as summarized by Fehr & Peers, 2023

As part of a separate project, the critical sidewalk gaps have been identified, and project bundles developed to address the gaps. The sidewalk gap project bundles will be added to project opportunities for the ATP.



Existing Pedestrian Facilities All Roadways in Region





Transit Facilities

LYNX is the transit provider for the MetroPlan Orlando Region. Each weekday, LYNX provides approximately 55,000 rides across 80 routes. In Fiscal Year 2022 (October 2021 to September 2022), approximately 16 million passenger trips were provided. Ridership significantly decreased during the COVID-19 pandemic, and while ridership continues to increase each month, it is still below the pre-pandemic peak of about 25 million annual riders. Existing fixed routes are shown on **Figure 10** with the average weekday boardings shown on **Figure 11**.

Bicycle and pedestrian facilities typically serve as first mile/last mile connectors to transit stops. Improving safety as people walk or bike to transit stops could help improve ridership and increase overall accessibility to transit in the region.

Mobility Trends

Micromobility has experienced significant growth and transformation in recent years. Micromobility refers to lightweight, often electric-powered vehicles designed for shortdistance trips, including electric bikes, electric scooters, and shared mobility services. These devices can be individually owned, or they can be part of a sharing service, like Bird, Lime, and Lyft.

These micromobility services can offer an alternative to traditional modes of transportation like cars and public transit. Users can locate and unlock shared vehicles through smartphone apps, making it easy to hop on a scooter or bike for short trips.

The rapid proliferation of micromobility has presented challenges, including issues related to parking, improper usage, and sidewalk clutter. Local governments have responded by implementing regulations and permitting processes to manage the influx of vehicles and ensure safety for both riders and pedestrians, but not all jurisdictions in the region have developed e-scooter and e-bike ordinances. The City of Orlando has the most robust bike and scooter share program in the region, with an average of 1,500 shared devices in operation on City of Orlando streets on a typical day, with over 520,000 trips taken in 2022, covering about 489,000 miles – demonstrating that most trips using shared mobility devices are relatively short trips. Additional information can be found on the City's website (linked here: https://www.orlando.gov/Initiatives/Bike-Share-Scooter-Share-Program) with ridership information provided by Populus (linked here: https://app.populus.ai/orlando/public/routes).

E-bikes and e-scooters, either privately owned or shared, can travel at much faster speeds than human powered bicycles and scooters, potentially creating safety hazards due to speed differential. Additionally, e-bikes can be significantly heavier than traditional bikes, potentially increasing the risk of injury or death in a collision with people walking or on bikes/scooters.

Low Speed Vehicles (LSV) can help enhance mobility options by providing a lower cost and more sustainable transportation mode, especially for short trips within communities that may be too long to walk and are not well served by other non-auto travel modes for a wide range



of the population. LSVs are similar to golf carts with slightly different regulations for LSVs versus golf carts, as shown in **Table 8**. Given the speed of many roadways within the region, people driving golf carts or LSVs within their communities may choose to drive on the sidewalk, creating the potential for conflicts people walking and bicycling. As an example, the City of Belle Isle became a golf cart community in 2020, allowing golf carts on all streets except McCoy Road. People are also allowed to drive golf carts on select sidewalks on roadways within the city, including Hoffner Avenue and Conway Road. In some places the width of the sidewalk does not allow for two-way travel for both people in golf carts and people walking or bicycling.

	Golf Cart	Low Speed Vehicle
Maximum Speed Allowed	20 mph	25 mph
Operator Requirements	14 years of age or older; no license or insurance required; no title or registration required	Driver's license and vehicle insurance; title and registration required
Allowable Roadways	Roadways designated for golf carts with a posted speed limit of 30 mph or less; may operate at dusk, night and dawn hours if equipped with headlights, brake lights, turn signals and windshield	Roadways with posted speed limit 35 mph or less; may operate on roadways with a 45-mph speed limit for short distances if there is no other route and not expressly prohibited
Allowable Crossings	To cross a FDOT or County facility, FDOT must review and approve the location and design of the crossing	Generally, no restrictions, but FDOT may prohibit the operation of LSV on or across a roadway if it is determined to cause a safety issue

Table 8: Distinction between Golf Carts and Low-Speed Vehicles

Source: Section 320.01 (41) of the Florida Statutes.

The Active Transportation Plan will consider these competing demands on the existing and planned infrastructure for walking and bicycling.



Existing Transit Routes





Existing Transit Ridership Fiscal Year 2022





Collision Analysis

The MetroPlan Orlando region has the unfortunate distinction of being one of the deadliest metropolitan areas for pedestrians in the country with our outcomes worsening over time. One of the goals of the ATP is to develop a safer bicycle and pedestrian network that improves transportation safety outcomes for vulnerable roadway users, including pedestrians, bicyclists, and other non-auto transportation system users. To support this goal, crash data reflective of 2018-2022 was reviewed and summarized in **Table 9** based on data from Signal4. This data reflects crashes that occurred anywhere within the MetroPlan Orlando region, including access-controlled facilities and parking lots. Data in the table is presented for each County as well as the regional total, and crash rates were normalized by population to allow for a comparison between counties. Data reflective of bicyclists and pedestrians generally does not include injuries that might be sustained while using the transportation system if a vehicle was not involved. For example, a pedestrian that trips and is injured might not be included, and a bicyclist that falls off their bike and hits their head on the curb, if that fall was unrelated to a vehicle activity, may not be included in crash report data.

Between 2018 and 2022, there were approximately 344,670 reported crashes in the region. It should be noted that:

- During the height of the pandemic, there may have been some under reporting of crashes that did not result in injuries or property damage as people were social distancing,
- Some KSI (crash which results in a fatality or severe injury) collisions may be underreported because not all serious injuries are visible (i.e., brain injuries),
- Fatalities that are reported within 30 days of the crash are recorded as a fatal crash; fatalities that are reported more than 30 days after the crash are not recorded as a fatal crash.

Of the total crashes occurring within the MetroPlan Orlando region, about 3 percent resulted in a fatality or severe injury, referred to as a KSI crash, accounting for all travel modes, with the most crashes and most crashes per person occurring in Orange County.

A much smaller number of crashes involve someone bicycling or walking, less than 3 percent. Although people walking and bicycling are involved in about 2.6 percent of all crashes, people walking and bicycling that are killed or severely represent over 15 percent of KSIs in the region.

Orange County has a higher severe and fatal crash rate on a per resident basis for pedestrians than Osceola and Seminole Counties, while Osceola County has the highest fatal crash rate for bicyclists when normalized by population.



Seminole Regional Orange Osceola County Total County County Variable Number Number Number Number (rate per 100k (rate per (rate per (rate per people) 100k 100k 100k people) people) people) **Total Population** 1,420,000 400.000 470.000 2,290,000 222,999 56,397 65,268 344,664 **Total Reported Collisions** (3, 141)(2, 820)(2,777)(3,010)1,778 8,074 11,058 1,206 Number of People Killed or Severely Injured (KSI) (114)(89) (97) (51)946 199 1,474 329 Number of People Killed (12.87)(13.32)(16.45)(8.47) 2,402 529 722 3,653 Collisions that involve a Bicyclist (33.83)(26.45)(30.72)(31.90)337 62 55 454 Number of Bicyclists Killed or Severely Injured (4.75) (3.10)(2.34)(3.97)8 49 17 74 Number of Bicyclists Killed (0.69)(0.85)(0.34)(0.65)3,482 799 1,076 5,357 Collisions that involve a pedestrian (49.04)(39.95)(45.79)(46.79)893 165 141 1,199 Number of Pedestrians Killed or Severely Injured (12.58)(8.25) (6.00)(10.47)286 54 49 389 Number of Pedestrians Killed (4.03) (2.70)(2.09)(3.40)

Table 9: Regional Collision Data (all roadways – 2018 to 2022)

Source: Signal4; data from 2018 - 2022

Bold indicates a crash rate above the regional average.



Crash trends by the characteristics of the roadway system were also reviewed, with the number of crashes involving a person walking or bicycling increasing as the number of vehicular travel lanes and the traffic volumes increases. There are many factors that contribute to this trend, such as:

- Roadways with high traffic volumes and multiple travel lanes tend to serve commercial corridors where transit is operated, and there is a high density of destinations.
- Multi-lane roadways (more than 7 lanes) tend to have higher posted speed limits (40+) and higher speed vehicle traffic that can increase crossing distance of roadways, increasing the exposure of people walking and bicycling to conflicts with vehicles, and increasing the reaction time of a person driving to react to someone crossing the roadway.

A heat map showing the locations within the MetroPlan Orlando Region with the number of reported crashes that result in a severe injury or fatality for people walking and bicycling is shown on **Figure 12**.



Pigure 12 Pedestrian and Bicyclist KSI Crash Locations (2018 – 2022)





LTS and PLOC

To evaluate where new and enhanced walking and bicycling facilities could improve accessibility within the MetroPlan Orlando region, a Level of Traffic Stress (LTS) analysis was conducted to assess the comfort for people bicycling on roadways within the region and a Pedestrian Level of Comfort (PLOC) analysis was conducted to assess the comfort of people walking on the transportation system. A technical memorandum was prepared to document the LTS and PLOC Methodology and is provided as **Appendix C.**

Level of Traffic Stress and Pedestrian Level of Comfort scores should not be construed as a predictor of facility use by people walking and bicycling. Area demographics and land uses along a corridor are better predictors of the volume of walking and bicycling that does and could occur. For example, in a low-density area where land uses are spread apart and most people have access to a vehicle, people may walk or bicycle for recreational purposes in the area, but not as a primary mode of travel. Conversely, in areas where complementary uses are within proximity and people have less access to vehicles, walking and bicycling activity is typically higher, even when low stress facilities are not available.

Bicycle Level of Traffic Stress

Inputs to the Level of Traffic Stress (LTS) analysis generally include:

- Type of bicycle facility present
- Speed limit of the roadway
- Traffic volumes on the roadway

LTS scores of 1 and 2 generally represent lower stress facilities than many people feel comfortable riding a bike on, while LTS 3 and 4 facilities are generally more stressful for people to use. Additional details are provided in the methodology memorandum. Shared Use Paths/trails and side paths are the least stressful bicycle facility type in the region, with paved shoulders and roadways with no bicycle facilities being the most stressful of roadways with bicycle lanes. A visual depiction of the LTS ratings is shown on **Image 8**. Results of the existing conditions LTS analysis are presented on **Figure 13** and summarized in **Table 10**.

MetroPlan Orlando Active Transportation Plan Existing Conditions





LTS 1

Most children can use this level confidently.



LTS 2

This is the level that will be tolerated by most adults.



LTS 3

This is the level that will be tolerated by trained and experienced cyclists who still prefer having their own dedicated space for riding.



LTS 4

This is the level that will be tolerated only by those with limited route or mode choice or trained and experienced cyclists that choose to ride under stressful conditions.

Image 8: Visual Depiction of Level of Traffic Stress

Table 10: LTS Score for MPO Network by Bicycle Facility Type (in miles of facility)

LTS Score	Shared Use Path/ Trail	Side Path	Bicycle Lanes/Paved Shoulder	No Bicycle Facility
1	128	342	66	121
2	-	-	28	74
3	-	-	82	245
4	-	-	522	800

Source: xGeographic; Fehr & Peers, 2023



Existing Bicycle Level of Traffic Stress





Pedestrian Level of Comfort

Inputs to the Pedestrian of Level of Comfort (PLOC) analysis generally include:

- Type of pedestrian facility present
- Distance between pedestrian facility and vehicular travel way
- Speed limit of the roadway
- Traffic volumes on the roadway

PLOC scores from one to five, with a PLOC 1 rating represents the lowest stress facility and primarily includes trails, side paths, and streets with sidewalks on both sides of the street as well as low volume and low speed vehicle travel. A PLOC 5 rating was reserved for roadways with no pedestrian facilities. More information about the PLOC methodology can be found in **Appendix C** and a graphic depiction of the PLOC scoring is shown on **Image 9**.



Image 9: Visual Depiction of Pedestrian Level of Comfort

Figure 14 displays the PLOC scores for the MetroPlan Orlando pedestrian network. **Table 11** summarizes the miles of pedestrian facilities by PLOC score. There is a higher percentage of lower stress (PLOC 1 or 2) pedestrian facilities than bicycle facilities, with about 33 percent of the facilities rated as PLOC 1 or 2. As previously mentioned, PLOC does not always correlate with where people are currently walking. Filling gaps, particularly on high stress facilities where people are already walking could be a good opportunity to improve pedestrian comfort in the region.



PLOC	Shared Use Path/ Trail	Side Path	Sidewalks Both Side	Sidewalks One Side	No Sidewalks
1	128	342	166	-	-
2	-	-	396	88	-
3	-	-	250	195	-
4	-	-	260	85	-
5	-	-	-	-	527

Table 11: PLOC Score for MPO Network by Pedestrian Facility Type (in miles of facility)

Source: xGeographic; Fehr & Peers, 2023



Existing Pedestrian Level of Comfort





Travel Access Analysis

A travel access analysis was conducted to identify locations in the region that have a high level of access to a variety of destinations via low stress walking and bicycling facilities, and parts of the region that may have high levels of access, but only on high-stress facilities. Analysis results will help guide where lower stress walking and bicycling facilities would be provided.

Based on feedback from the public as well as the steering committee, the travel access analysis considered how accessible a variety of key destinations are from the surrounding area, with the following destination types considered locations where travel access would be prioritized:

- Public Schools
- Transit Facilities, such as LYNX stops and SunRail stations
- Parks, including neighborhood parks and regional parks
- Jobs, based on the location of businesses in the xGeographic Wave database
- Shopping, including grocery stores

The distance that an average person might be able to bicycle within different time periods was based on an average biking speed of 10 miles per hour, meaning that it would take an average person about 30 minutes to travel 5-miles on their bicycle. For walking access, an average walking speed of 3 miles per hour was used. Some people may bike or walk faster or slower than the averages, with these speeds selected for planning purposes. For each destination type, the areas that could be reached within 1-5 minutes, 6-15 minutes, and 16-30 minutes were assessed. Where there are sidewalk gaps, it was set as a walking barrier with no walking trips able to pass by the area without a sidewalk. A similar impedance was not applied for bicycle travel. With all land uses combined, the allowable score ranges from 0 to 5. The results shown on **Figure 15** for bicycling accessibility and **Figure 16** for pedestrian accessibility, meaning that the higher the total accessibility score the, the higher the level of access via bicycling and walking.

To account for the comfort of walking and bicycle facilities provided, the underlying LTS and PLOC rating were then factored into the analysis. Based on the stress of the routes, a score was assigned to assess the overall comfort of walking and biking to various destinations within the region. Areas that are either inaccessible or only accessible via high stress networks received a lower score than areas that are accessible via lower stress networks, with the results shown on **Figure 17** for bicycling accessibility and **Figure 18** for pedestrian accessibility. Roadways were rated with one of four scores:



- *Low LTS/PLOC and High Access* these are roadways where there are many destinations within the travel buffers (above average access score), and the route is comfortable (average LTS/PLOC score of 2 or better).
- *Low LTS/PLOC and Low Access* these are roadways where there are not that many destinations within the travel buffers (lower than average access score), but the route is comfortable (average LTS/PLOC score of 2 or better).
- *High LTS/PLOC and Low Access* these are roadways where there are not that many destinations within the travel buffers (lower than average access score), and the route is uncomfortable (average LTS/PLOC score greater than 2).
- *High LTS/PLOC and High Access* these are roadways where there are many destinations within the travel buffers (above average access score), but the route is uncomfortable (average LTS/PLOC score greater than 2).

The overall accessibility to different land use types by primarily low stress networks (route average LTS or PLOC is 2 or better) is summarized in Table 12 for a 15-minute travel time and Table 13 for a 30-minute travel time. In the region, about 28 percent of schools are accessible via a 15-minute low stress walking network and about 10 percent are accessible via a 15 minute-low stress bicycling network. Parks are the most accessible land use by both walking and bicycling travel modes. This is likely due to the placement of parks within neighborhoods as development occurs. Shopping destinations are the least accessible for people walking, with only about 12 percent of shopping destinations accessible via a 15minute walk. This is likely due to the placement of many shopping centers on arterial roadway. About 20 percent of transit stops in the region are considered accessible by a 15minute walk, with less than 2 percent accessible by a 15-minute bike ride. When travel time assumptions are increased, the number of walkable and bikeable destinations via a low stress route increases. For example, the number of parks accessible in a 30-minute walk increases to about 76 percent of parks in the region. Access to shopping centers also doubles and access to transit facilities almost doubles. There are also some modest gains for the bicycling access sheds, with parks remaining the most accessible land use in the region via bicycling.

It is important to note the distance traveled within a 15 (or 30) minute walk shed is considerably shorter than that of a 15-minute bicycle shed (since the assumed travel speed is 3 mph for pedestrians and 10 mph for bicyclists). This likely contributes to the result that facilities are generally more accessible via low-stress networks for pedestrians compared to bicyclists. This also suggests that low-stress accessibility decreases as trips get longer as consistently comfortable facilities are not provided. Additionally, due to the high granularity of the data, there may be short segments identified as uncomfortable or posing as a barrier to access, such as where no designated or controlled crossing locations are present in proximity to the nearby land uses.



FIGURE 15 Existing Bicycle Accessibility Score





Existing Pedestrian Accessibility Score





Existing Bike Access and Comfort Summary





Existing Pedestrian Access and Comfort Summary





Land Use Type	Total within Region	Total Accessible on walking network	Percent Accessible on walking network	Total Accessible on biking network	Percent Accessible on biking network
Schools	317	90	28%	31	10%
Transit Facilities	4,280	877	20%	97	2%
Parks	817	368	45%	102	12%
Jobs	2,704	663	25%	157	6%
Shopping	1,776	210	12%	48	3%

Table 12: Existing Travel Access Summary Via Predominately Low-Stress Network* – 0 -15 Minute Travel Time

*Predominately low-stress network" definition: Average PLOC or LTS of all roads within shed is less than or equal to 2 Source: xGeographic; Fehr & Peers, 2023

Table 13: Existing Travel Access Summary Via Predominately Low-Stress Network* – 0 -30 Minute Travel Time

Land Use Type	Total within Region	Total Accessible on walking network	Percent Accessible on walking network	Total Accessible on biking network	Percent Accessible on biking network
Schools	317	142	45%	50	16%
Transit Facilities	4,280	1,597	37%	128	3%
Parks	817	618	76%	154	19%
Jobs	2,704	1152	43%	277	10%
Shopping	1,776	415	23%	78	4%

*Predominately low-stress network" definition: Average PLOC or LTS of all roads within shed is less than or equal to 2 Source: xGeographic; Fehr & Peers, 2023



Accessibility was also measured in disadvantaged communities (meeting 4 or more of the factors listed previous in the Regional Overview section, starting on Page 10). Any travel shed whose area covered at least 50% of a disadvantaged community was flagged as a shed within a disadvantaged community. **Table 14** and **Table 15** show the number of predominately accessible facilities within disadvantaged communities for 15 and 30-minute travel times, respectively. It is apparent that disadvantaged communities are less likely to be found in low stress travel sheds compared to those that are not.

Land Use Type	Total within Region	Total Accessible on walking network	Percent Accessible on walking network	Total Accessible on biking network	Percent Accessible on biking network
Schools	317	27	9%	3	1%
Transit Facilities	4,280	570	13%	25	1%
Parks	817	100	12%	8	1%
Jobs	2,704	263	10%	38	1%
Shopping	1,776	91	5%	4	1%

Table 14: Existing Travel Access Summary Via Predominately Low-Stress Network within Disadvantaged Communities – 0-15 Minute Travel Time

Source: xGeographic; Fehr & Peers, 2023

Table 15: Existing Travel Access Summary Via Predominately Low-StressNetwork within Disadvantaged Communities – 0-30 Minute Travel Time

Land Use Type	Total within Region	Total Accessible on walking network	Percent Accessible on walking network	Total Accessible on biking network	Percent Accessible on biking network
Schools	317	39	12%	5	2%
Transit Facilities	4,280	896	21%	49	1%
Parks	817	165	20%	14	2%
Jobs	2,704	445	16%	46	2%
Shopping	1,776	160	9%	8	0%

Source: xGeographic; Fehr & Peers, 2023

The population characteristics of each travel shed were also reviewed. **Table 16** summarizes the average population within the travel shed for each of the destination land uses, with



Table 17 summarizing the percent of that population that resides in a disadvantagedcommunity. In general, populations within predominantly accessible areas are higher whenthey are not within disadvantaged communities.

Land Use Type	Avg. Pop within 0-15 min walk shed	Avg. Pop within 0-15 min bike shed	Avg Pop between 0-30 min walk shed	Avg Pop between 0-30 min bike shed
Schools	2,260	9,767	9,056	24,568
Transit Facilities	3,503	7,756	12,346	18,256
Parks	2,004	6,300	7,470	22,440
Jobs	2,246	5,508	11,564	18,257
Shopping	2,986	9,702	10,423	25,109

Table 16: Average Population in Low Stress Travel Sheds

Source: xGeographic; Fehr & Peers, 2023

Land Use Type	Avg. Pop within 0-15 min walk shed	Avg. Pop within 0-15 min bike shed	Avg Pop between 0-30 min walk shed	Avg Pop between 0-30 min bike shed
Schools	2,823	11,105	8,259	457
Transit Facilities	2,948	809	8,460	837
Parks	2,200	2,426	6,626	338
Jobs	2,213	6,359	7,534	466
Shopping	2,800	347	8,505	347

Table 17: Disadvantaged Community Population in Low Stress Travel Sheds

Source: xGeographic; Fehr & Peers, 2023



Planned Facilities

As a starting point to the identification of new active transportation facilities in the region, the planned bicycle facility types were documented as shown on **Figure 19** for on-street facilities and **Figure 20** for off-street facilities, and summarized in **Table 18**. This planned network has been confirmed by local agencies in the region in early August 2023 and will serve as a starting point for the identification of new facilities in the region. Some new planned facilities were noted at the August 2023 Technical Advisory Workshop and will be incorporated into the Active Transportation Plan.

Facility Type	Orange	Osceola	Seminole	Total
Shared-Use Path/Trail	22	2	0	24
Side Path	237	244	142	623
Wide sidewalks	0	0	0	0
Bike Lane (4 ft +)	150	80	13	243

Table 18: Planned Facility Types on MPO Network

Source: xGeographic; Fehr & Peers, 2023

A preliminary future year accessibility analysis was also conducted to see how planned improvements could improve accessibility, with the results shown on Figure 21 for bicycling and Figure 22 for walking. The number of destinations accessible via a predominately low stress network was also calculated for the future planned system, with the results shown in Table 19 for a 15-minute low stress travel buffer and Table 20 for a 30-minute low stress travel buffer. Overall, the planned system will increase the number of low stress routes to key destinations within the region, although many destinations will continue to not be accessible via a low stress walking and bicycling network.



FIGURE 19 Planned On-Street Bicycle Facilities





FIGURE 20 Planned Off-Street Facilities



10 miles

____ Side-Path / Shared-Use Path



FIGURE 21 FUTURE Bicyclist Accessibility with Planned Improvements





FIGURE 22 FUTURE Pedestrian Accessibility with Planned Improvements





Table 19: Future Planned System Travel Access Summary Via Predominately
Low-Stress Network* – 15 Minute Travel Time

Land Use Type	Total within Region	Total Accessible on walking network	Percent Accessible on walking network	Total Accessible on biking network	Percent Accessible on biking network
Schools	317	190	60%	60	19%
Transit Facilities	4,280	1,659	39%	334	8%
Parks	817	557	68%	191	23%
Jobs	2,704	1,504	56%	532	20%
Shopping	1,776	941	53%	261	15%

*Predominately low-stress network" definition: Average PLOC or LTS of all roads within shed is less than or equal to 2

Source: xGeographic; Fehr & Peers, 2023

Table 20: Future Planned System Travel Access Summary Via Predominately Low-Stress Network* – 30 Minute Travel Time

Land Use Type	Total within Region	Total Accessible on walking network	Percent Accessible on walking network	Total Accessible on biking network	Percent Accessible on biking network
Schools	317	188	59%	50	16%
Transit Facilities	4,280	1720	40%	296	7%
Parks	817	532	65%	133	16%
Jobs	2,704	1483	55%	475	18%
Shopping	1,776	857	48%	236	13%

*Predominately low-stress network" definition: Average PLOC or LTS of all roads within shed is less than or equal to 2 Source: xGeographic; Fehr & Peers, 2023



Public Participation

Community outreach and engagement is a critical component of the MetroPlan Orlando Regional Active Transportation Plan (ATP): Ride & Stride 2050 for both informing the public and key stakeholders about the effort and for soliciting their feedback.

Outreach and engagement are primarily focused on three different groups:

- Steering Committee
 - This diverse committee provided overall project guidance. We asked Steering Committee members to support public outreach efforts through their networks. Four steering committees have been held as of July 2023.
 - The first meeting introduced the overall project, specific tasks, and public engagement strategies.
 - The second reviewed the preliminary feedback from the public engagement process and discussed the approach to the LTS and PLOC analysis and presented the framework for the Travel Access analysis.
 - The third meeting presented the results of the initial public engagement survey as well as the results of the accessibility analysis. The framework for the toolbox of strategies was also presented.
 - The fourth meeting was an in-person workshop format where potential new projects, including new trail segments, potential crossing enhancements, corridor implements, safety improvements, and corridors for target speed reduction were presented for feedback from the TAC. Potential project prioritization criteria was also discussed and feedback received.
- MetroPlan Orlando committees, with a focus on the TAC and CAC
 - Project status updates were provided at regular intervals at CAC and TAC meetings. Opportunities for more in-depth feedback and comments were offered during project workshops. Feedback received during these status update meetings and workshops was considered and incorporated into the overall project.
 - The first set of workshops were held in October 2022 and feedback from the TAC and CAC have been incorporated into the base mapping and overall approach.
 - The second set of workshops were held in August 2023, and feedback on the draft 2050 ATP projects will be incorporated into the MetroPlan Orlando



Regional Active Transportation Plan (ATP): Ride & Stride 2050. Additionally, since the October 2022 workshop, some agencies have updated their local Active Transportation Plan; should GIS layers reflecting their updated planned project list be provided by early September, it will be incorporated in the plan and associated regional GIS database.

- General Public
 - General public engagement occurred in the form of online surveys and interactive GIS based maps. An email list of potential interested parties was developed based on feedback from the Steering Committee as well as TAC/CAC to disseminate project information. A request for feedback was conducted during February and March 2023. A detailed summary of the first public engagement is provided as Appendix E. Another round of feedback requests will be conducted in late 2023 and the summary of that engagement will be appended to this document as Appendix F.